

PEAKWORKS

FALL INTO PEAKWORKS SAVINGS

We have selected the items below to ensure that when your customers are doing fall clean-ups, they have the right fall protection for the job.

**SALE ENDS
OCTOBER 31, 2015
OR AS SUPPLIES LAST.**

Storage Pail



Compliance Harness



Vertical Lifeline

ROOFER'S KITS

- All PeakWorks roofer's kits components are certified to the applicable CSA standards.
- We offer a wide range of prepackaged fall protection kits that include specific full body harnesses and connector, a shock absorbing lanyard with panic rope grab and anchor.
- Kits come in waterproof pail or a breathable bag for convenient storage.

Reusable Roof Bracket



Shock Absorbing Lanyard

ROPE GRABS

- All PeakWorks rope grabs are certified to CSA Z259.2.5-2012 and meet ANSI Z359 standards.
- Our rope grabs are equipped with a panic lock feature which "bites" onto the rope even if the user mistakenly pushes the cam up, ensuring that the rope grab will lock and arrest the fall in any situation.
- Rope grabs offer the most cost-effective fall protection solution when working at height.



V83010

V83011



PEAKWORKS

FALL INTO PEAKWORKS SAVINGS

We have selected the items below to ensure that when your customers are doing fall clean-ups, they have the right fall protection for the job.

**SALE ENDS
OCTOBER 31, 2015
OR AS SUPPLIES LAST.**



V84014050

VERTICAL LIFELINES

- All PeakWorks lifelines are certified to CSA Z259.2.5-2012 and meet ANSI Z359 standards.
- Lifelines are specially designed from rope made using high-strength polysteel.
- Our vertical lifelines are all 5/8" (16 mm) in diameter.
- Minimum breaking strength 6,000 lbs (27 kN).
- All our lifelines have a back splice at the trailing end to prevent the rope grab from coming off the end of the lifeline.

ROOF BRACKETS

- PeakWorks offers a wide range of anchor systems including single-use and reusable roof anchors.
- As with all fall protection products, anchors must be inspected by a competent person at a minimum annually.
- All our anchors are built with a minimum tensile strength of 5,000 lbs (22 kN).
- All our anchors meet or exceed CSA Z259.15 and
- ANSI Z359.18 standards and OSHA requirements.
- 310 lb (141 kg) capacity for 1 worker (combined weight of person, tools, clothing, etc.).



V8229001



V8229100



V8229104



JET GROUP